



## DARK CAN 100



### LUMINAIRE SPECIFICATION

<b>Height</b>	Refer to line drawing
<b>Bezel</b>	Ø95mm
<b>Length</b>	170mm
<b>Mounting</b>	Surface, pendant rod and pedant wire options
<b>Luminaire material</b>	Aluminium with textured powder coat finish
<b>Light source</b>	LED with interchangeable LED and optics
<b>Driver</b>	Integral
<b>IP Rating</b>	IP20 & IP44 Options
<b>Accessories</b>	Honeycomb louvre Frosted lens Spread lens

### LED SPECIFICATION

<b>LED</b>	Citizen high intensity		
<b>Typical lumen output<sup>(i)</sup></b>	CRI >90		
	LED Source	Delivered	
<b>9W</b>	1012 lm	904 lm	
<b>12W</b>	1362 lm	1221 lm	
<b>CCT</b>	2700K, 3000K, 4000K		
<b>CRI</b>	>90Ra		
<b>Binning</b>	2 Step		
<b>Optics</b>	15°, 25°, 35°, 50°		
<b>Lifetime (L70)</b>	50,000hrs based on LM-80 & TM-21 applicable test data		
<b>Driver requirement</b>	Constant current		
<b>Drive current</b>	B / 9W	: 250mA	
	C / 12W	: 350mA	
<b>Forward voltage</b>	36VDC		

### REFLECTOR OPTIONS



### ORDERING INFORMATION

example 245L25.1CG33B9C-R20-H

BEAM ANGLE	FINISH	REFLECTOR	LED CCT	DRIVER	LED VERSION	IP RATING	MOUNTING	ACCESSORIES
245L15 15°	1 White	SC Silver chrome	2 2700K	2 Phase dimming	B9C 9W CRI >90	IP20	Surface	-H Honeycomb louvre
245L25 25°	2 Black	DC Dark chrome	3 3000K	3 0-10V dimming	B12C 12W CRI >90	4 IP44	-R10 1m Pendant rod	-FR Frosted lens
245L35 35°	7 Silver	MB Matt black	4 4000K	4 DALI dimming			-R20 1m Pendant rod	-SL Spread lens
245L50 50°		MW Matt white						
		CG Champagne gold					-W10 1m Pendant wire	
							-W20 2m Pendant wire	
							-W30 3m Pendant wire	