





# NON DIMMING CV LED DRIVER



## SPECIFICATION

<b>4713.24120</b>	
<b>Dimensions</b>	108 x 42 x 23mm
<b>Weight</b>	150g
<b>Type</b>	Constant voltage
<b>Output voltage</b>	24V
<b>Output current</b>	1250mA
<b>Output power</b>	30W
<b>Dimming</b>	-
<b>IP Rating</b>	IP20
<b>Input</b>	180-260VAC 50/60Hz, 0.153A@230V
<b>Power factor</b>	> 0.95 at full load
<b>Efficiency</b>	85% at full load
<b>Operating temperature</b>	-20...+45°C
<b>Material</b>	94V-0 PC fire retardant
<b>Safety</b>	Short circuit and over voltage
<b>Compliance</b>	Safety : EN61347-2-13.IP40 EMC : EN55015, EN61000-3-2, EN61000-4-2,3,4,5,6,8,11, EN61547

## EXPECTED FAILURE RATE & LIFE-TIME

<b>Failure rate</b>	tc @ Max 80°C : <0.2% / 1000hrs	
<b>Life-time</b>	ta 35°C	ta 50°C
	>70,000hrs	>50,000hrs

The LED Driver is designed for a minimum life-time stated above with a probability of less than 10% failure.

## ORDERING INFORMATION

4713.24120 30W 24V Non dimming constant voltage LED driver