



FLEX 5X6 VERTICAL DOMED



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP65
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
STANDARDS	EN/AS/NZS 60598-2-1, 62031, 62471
WARRANTY	5 Years

MONO CCT

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>30 mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver
ADHESIVE BACKING ^(a)	If backing is used, the flex will not fit into the aluminium profile accessory

	LED SPECIFICATION			LUMEN PACKAGE lm/m							
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K	
SF04	4 W/m	7 m	25 mm	330	432	472	508	520	534	526	
SF08	8 W/m	5 m	25 mm	550	720	788	846	862	888	876	
SF12	12 W/m	4 m	25 mm	764	998	1092	1176	1198	1232	1216	

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	ADHESIVE BACKING	LENGTH
63S0506VD Neon Flex 5X6 VD	1 White	C18 1800K C24 2400K C27 2700K C30 3000K C35 3500K C40 4000K C60 6000K	SF04 4 W/m (7m max. V24) SF08 8 W/m (5m max. V24) SF12 12 W/m (4m max. V24)	E End	5 IP65	003 0.3m 010 1m 030 3m 050 5m 100 10m	A 3M Backing Included ^(a)	.XXXX Length in mm
63S0506VD	1				5		OPTIONAL	

SINGLE COLOUR

SPECIFICATION

MINIMUM BEND DIAMETER	>30 mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver
ADHESIVE BACKING ^(a)	If backing is used, the flex will not fit into the aluminium profile accessory

	Wattage	Max. Length	Cut Interval	RED	GREEN	BLUE
S05	5 W/m	5 m	50 mm	180	530	124
S09	9 W/m	3 m	50 mm	320	956	224
S12	12 W/m	3 m	50 mm	430	1276	300
S14	14 W/m	2.5 m	50 mm	500	1484	350

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	ADHESIVE BACKING	LENGTH
63S0506VD Neon Flex 5X6 VD	1 White	RED Red GREEN Green BLUE Blue	S05 5 W/m (5m max. V24) S09 9 W/m (3m max. V24) S12 12 W/m (3m max. V24) S14 14 W/m (2.5m max. V24)	E End	5 IP65	003 0.3m 010 1m 030 3m 050 5m 100 10m	A 3M Backing Included ^(a)	.XXXX Length in mm
63S0506VD	1				5		OPTIONAL	

ACCESSORIES

TYPE	Aluminium push in profile
MOUNTING	Surface mount

ORDERING INFORMATION

MODEL	FINISH	LENGTH
63S0506X	5PP Aluminium	0020 20mm 1000 1000mm 2000 2000mm
63S0506X	5PP	

