



HONEYCOMB FLEX 10X10 MULTI



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
STANDARDS	EN/AS/NZS 60598-2-1, 62031, 62471
WARRANTY	5 Years

MONO CCT

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>200mm in both planes
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver

	LED SPECIFICATION			LUMEN PACKAGE lm/m						
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K
S05	5 W/m	6 m	55.56 mm	32	42	46	48	50	52	50
S10	10 W/m	4 m	55.56 mm	64	84	92	100	100	104	102

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010HCM Honeycomb Flex 10x10 M	2 Black	C18 1800K	S05 5 W/m (6m max. V24)	E End	7 IP67	003 0.3m	.XXXX
		C24 2400K	S10 10 W/m (4m max. V24)	B Bottom		010 1m	Length in mm
		C27 2700K		SL Side Left		030 3m	
		C30 3000K		SR Side Right		050 5m	
		C35 3500K				100 10m	
		C40 4000K					
		C60 6000K					
63S1010HCM	2				7		

HIGH OUTPUT MONO CCT

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>200mm in both planes
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver

	LED SPECIFICATION			LUMEN PACKAGE lm/m						
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K
S10	10 W/m	4 m	55.56 mm	76	96	104	112	116	120	116

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010HCHOM Honeycomb Flex 10x10 M	2 Black	C18 1800K	S10 10 W/m (4m max. V24)	E End	7 IP67	003 0.3m	.XXXX
		C24 2400K		B Bottom		010 1m	Length in mm
		C27 2700K		SL Side Left		030 3m	
		C30 3000K		SR Side Right		050 5m	
		C35 3500K				100 10m	
		C40 4000K					
		C60 6000K					
63S1010HCHOM	2		S10		7		