




FLEX HC 10X10 MULTI BEND



Horizontal Bending



Vertical Bending



LUMINAIRE SPECIFICATION

Width	10 mm
Height	10 mm
Maximum length	5 W/m : 6 m 10 W/m : 4 m
Cut interval	55.6 mm
Minimum bend diameter	Vertical : Ø100 mm Horizontal : Ø150 mm
Material	Silicone with integral honeycomb anti glare feature
Mounting	Surface
IP Rating	IP67
Protection	UV, flame, salt and chlorine resistant
Standards	EN/AS/NZS 60598-2-1, 62031, 62471
Warranty	5 Years

LED SPECIFICATION

LED Wattage	5 W/m and 10 W/m options				
CCT	See options table below				
CRI	>90Ra				
Lumen package	Power	2700K	3000K	4000K	6500K
	5 W/m (6 m max.)	57 lm/m	61 lm/m	64 lm/m	63 lm/m
	10 W/m (4 m max.)	114 lm/m	122 lm/m	128 lm/m	127 lm/m
Binning	3 Step				
Lifetime (L70)	50,000hrs based on LM-80 & TM-21 applicable test data				
Driver requirement	Constant voltage				
Voltage	24VDC				

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	CONNECTOR IP	CABLE LENGTH	LENGTH
63S1010HCM Neon Flex 10 HC	2 Black	C18 1800K C24 2400K C27 2700K C30 3000K C35 3500K C40 4000K C60 6000K	S05 5 W/m (6 m max.) S10 10 W/m (4 m max.)	E End B Bottom SL Side Left SR Side Right	7 IP67	003 0.3m 010 1m 030 3m 050 5m 100 10m	.XXXX Length in mm
63S1010HCM	2				7		