




FLEX 10X10 VERTICAL DOMED



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
STANDARDS	EN/AS/NZS 60598-2-1, 62031, 62471
WARRANTY	5 Years

MONO CCT

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	100mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver

	LED SPECIFICATION			LUMEN PACKAGE lm/m						
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K
S05	5 W/m	10 m	50 mm	280	368	402	432	440	454	448
L05	5 W/m	20 m	50 mm	280	368	402	432	440	454	448
S10	10 W/m	5 m	50 mm	540	706	772	830	846	872	860
L10	10 W/m	10 m	50 mm	540	706	772	830	846	872	860

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010VD Neon Flex 10x10 VD	1 White	C18 1800K	S05 5 W/m (10m max. V24)	E End	7 IP67	003 0.3m	.XXXX Length in mm
		C24 2400K	L05 5 W/m (20m max. C24)	B Bottom		010 1m	
		C27 2700K	S10 10 W/m (5m max. V24)	SL Side Left		030 3m	
		C30 3000K	L10 10 W/m (10m max. C24)	SR Side Right		050 5m	
		C35 3500K				100 10m	
		C40 4000K					
		C60 6000K					
63S1010VD	1				7		

HIGH OUTPUT MONO CCT

SPECIFICATION




CRI	>90 Ra
MINIMUM BEND DIAMETER	>100mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver

	LED SPECIFICATION			LUMEN PACKAGE lm/m						
	Wattage	Max. Length	Cut Interval	1800K	2400K	2700K	3000K	3500K	4000K	6000K
S10	10 W/m	7 m	62.5 mm	826	1082	1170	1272	1298	1296	1316
L10	10 W/m	15 m	50 mm	624	816	884	960	980	980	994

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010HOVD Neon Flex 10x10 VD	1 White	C18 1800K	S10 10 W/m (7m max. C24)	E End	7 IP67	003 0.3m	.XXXX Length in mm
		C24 2400K	L10 10 W/m (15m max. C24)	B Bottom		010 1m	
		C27 2700K		SL Side Left		030 3m	
		C30 3000K		SR Side Right		050 5m	
		C35 3500K				100 10m	
		C40 4000K					
		C60 6000K					
63S1010HOVD	1				7		

FLEX 10X10 VERTICAL DOMED



SPECIFICATION	
MATERIAL	Silicone
MOUNTING	Surface
IP RATING	IP67
BINNING	3 Step
LIFETIME (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
DRIVER REQUIREMENT	24VDC Constant voltage
PROTECTION	UV, flame, salt and chlorine resistant
STANDARDS	EN/AS/NZS 60598-2-1, 62031, 62471
WARRANTY	5 Years

TUNABLE WHITE

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>100 mm
DIMMING REQUIREMENT	C24 PWM Output driver only V24 Voltage reduction/amplitude or PWM output driver

LED SPECIFICATION				LUMEN PACKAGE lm/m						
Wattage	Max. Length	Cut Interval		1800K	2400K	2700K	3000K	3500K	4000K	6000K
CT08	2x8 W/m	5 m	50 mm	352	494	542	570	574	580	562

* Rated wattage is maximum wattage per channel. Combined power must also not exceed this value.

ORDERING INFORMATION

MODEL	JACKET	CCT	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010VD Neon Flex 10x10 VD	1 White	C18 1800K	24 2400K	CT08 2x8 W/m (5m max. V24)	E End B Bottom SL Side Left SR Side Right	7 IP67	003 0.3m	.XXXX
		C24 2400K	27 2700K				010 1m	Length in mm
		C27 2700K	30 3000K				030 3m	
		C30 3000K	35 3500K				050 5m	
		C35 3500K	40 4000K				100 10m	
		C40 4000K	60 6000K					
63S1010VD	1			CT08		7		

WARM DIM

SPECIFICATION

CRI	>90 Ra
MINIMUM BEND DIAMETER	>100 mm
DIMMING REQUIREMENT	VR Voltage reduction/amplitude dimming driver required (not PWM compatible)

LED SPECIFICATION				LUMEN PACKAGE lm/m	
Wattage	Max. Length	Cut Interval		2700K	3000K
10R	10 W/m	5 m	50 mm	536	584

ORDERING INFORMATION

MODEL	JACKET	CCT	CCT	LED TYPE	CABLE ENTRY	IP RATING	CABLE LENGTH	LENGTH
63S1010VD Neon Flex 10x10 VD	1 White	C2718W 2700-1800K	10R 10 W/m (5m max. VR)	10R 10 W/m (5m max. VR)	E End B Bottom SL Side Left SR Side Right	7 IP67	003 0.3m	.XXXX
		C3018W 3000-1800K					010 1m	Length in mm
							030 3m	
							050 5m	
							100 10m	
63S1010VD	1			10R		7		