


Description:

Surface mounted wall light with feature crackle glass. Available in 4W or 6W CREE XHP-50 Gen 2, various colour temperatures and base finishes. IP44, Machined Solid Metal base, 100mm Frosted Sphere Glass Ball, Pre-fitted exterior rated 500mm lead, surface 'Covert Mounting System'.



Technical:

| | | | |
|-------------------------------|--------------------------|------------------|-----------------------------------|
| LED TYPE | XHP-50 Gen 2 | CONTROL GEAR | REMOTE |
| RATED POWER | 4W - 6W | DIMMING PROTOCOL | DALI - 0-10V - PHASE DIM - ON/OFF |
| CRI | 80 | CABLE LENGTH | 500MM STANDARD LENGTH |
| BEAM ANGLES | NOMINATED IN TABLE BELOW | MOUNTING OPTIONS | SURFACE |
| INPUT POWER / FORWARD VOLTAGE | 350mA - 700mA / 6V | WEIGHT | 0.5KG |
| NOMINAL LUMENS | 400lm - 800lm | HARDWARE | GLASS, GLAND, CABLE |
| IP RATING | IP44 | CONSTRUCTION | MACHINED METAL & HEATSINK |
| COLOUR TEMPERATURE | 2700K - 3000K - 4000K | WARRANTY | 2 YEARS |

Product Generator: example 1154CC-AB-D-30-SM-4W-DALI-N/A

| Model | Finish | Beam Angle | CCT | Mounting | Wattage | Dimming | Accessory |
|----------|------------------|------------|----------|------------|------------|---------|-----------|
| NL1154CC | AB Aged Brass | D Diffused | 27 2700K | SM Surface | 4W / 350mA | DALI | N/A |
| | BR Brushed Brass | | 30 3000K | | 6W / 700mA | 0-10V | |
| | PB Black | | 40 4000K | | | Phase | |
| | PW White | | | | | On/Off | |
| | CC Custom | | | | | | |

| | | | | | | | |
|--------|---|---|---|---|---|---|---|
| NL1154 | - | - | - | - | - | - | - |
|--------|---|---|---|---|---|---|---|