

Description:

Suspended pendant, 3W XP-G3, available in various colour temperatures, IP20, various beam angles, finished in Brass (Aged), with or without pre-fitted Honey Comb Baffle, Double sealed body with Nitrile O-Rings, pre-fitted 1500mm lead, remote constant current.



Technical:

LED TYPE	CREE XLAMP XP-G3	CONTROL GEAR	REMOTE
RATED POWER	3W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE CEILING
INPUT POWER	700mA / 3V	WEIGHT	0.5KG
NOMINAL LUMENS	380lm	HARDWARE	GLASS LENS, O-RING, GLAND, CABLE
IP RATING	IP20	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example 1202-AB-M-30-S-3W-DALI-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1202	AB Aged Brass	N Narrow	27 2700K	S Suspended 1500mm	3W / 700mA	DALI	HC Honeycomb Louver
	CC Custom	M Medium	30 3000K	SC Suspended Custom		0-10V	
		W Wide	40 4000K			Phase	

NL1202	-		-		-		-	
--------	---	--	---	--	---	--	---	--