

## Description:

Belonging to the **Firefly Family** range, the Firefly Pendant offers a simple, clean aesthetic available in various colour temperatures, optics, finishes and control options. The Firefly Family offers a variety of products suitable for various applications. The products contain the same LED chip and optics for a consistent approach. Supplied with matching ceiling rose and cable in 3 standard drop lengths of 500mm, 1000mm and 1500mm. The Family also consists of a **Micro**, **XL** and **Deco** range creating a full suite of products.



## Technical:

LED TYPE	XHP-50 Gen 2	CONTROL GEAR	REMOTE
RATED POWER	4W / 6W / 9W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE MOUNTED
INPUT POWER / FORWARD VOLTAGE	350mA / 700mA / 1050mA - 8V / 9V	WEIGHT	0.6KG
NOMINAL LUMENS	406lm / 812lm / 1218lm	HARDWARE	GLASS LENS, O-RING, GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

## Product Generator: example 7008-AB-M-30-S500-4W-DALI-HC

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL7008	AB Aged Brass	N Narrow 10°	27 2700K	Suspended 500mm	4W / 350mA	DALI	HC Honeycomb Louver
	BR Brushed Brass	M Medium 21°	30 3000K	Suspended 1000mm	6W / 700mA	0-10V	DL Diffuser Lens
	PB Black	W Wide 33°	40 4000K	Suspended 1500mm	9W /1050mA	Phase	EL Elliptical Lens
	PW White					On/Off	SL Spread Lens
	CC Custom						RS Rod suspension

NL7008	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---