

Description:

Belonging to the **Firefly Family** range, the Firefly Deco Pendant offers a simple, clean aesthetic with a decorative feature available in various colour temperatures, optics, finishes and control options. The products contain the same LED chip and optics for a consistent approach. Supplied with matching ceiling rose and cable in 3 standard drop lengths of 150mm, 350mm and 500mm. The Family also consists of a **Micro**, **XL** and **Firefly Standard** range creating a full suite of products.



Technical:

LED TYPE	XHP-50 Gen 2	CONTROL GEAR	REMOTE
RATED POWER	4W / 6W / 9W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE MOUNTED
INPUT POWER	350mA / 700mA / 1050mA - 6V	WEIGHT	1-2KG
NOMINAL LUMENS	495lm - 1485lm	HARDWARE	GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example 7038-BR-M-30-1-4W-1-1

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL7038	AB Aged Brass	N Narrow 10°	27 2700K	1 Suspended 150mm	4W / 350mA	1 DALI	1 Honeycomb Louver
	BR Brushed Brass	M Medium 21°	30 3000K	2 Suspended 350mm	6W / 700mA	2 0-10V	2 Diffuser Lens
	PB Black	W Wide 33°	40 4000K	3 Suspended 500mm	9W /1050mA	3 Phase	3 Elliptical Lens
	PW White			4 Suspended custom		4 On/Off	4 Spread Lens
	CC Custom						5 Wire suspension

NL7038	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---