

**Description:**

Deep Baffled Inground Uplight, 9Watt Bridgelux V8 Gen-7, Various colour temperatures, IP67 rated, Machined solid brass body, Stainless Steel or Machined Solid Brass (Aged) Face Plate, Machined Copper Heat Sink, Double sealed Silicon O-Ring, M12 sealed cable gland, double insulated exterior rated pre-fitted cable, mounting by pre-installation mounting 'Block-Out' (supplied complete)



**Technical:**

LED TYPE	Bridgelux V8 Gen-7	CONTROL GEAR	REMOTE
RATED POWER	9W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	RECESSED - FLOOR / WALL
INPUT POWER / FORWARD VOLTAGE	350mA / 17.3V	WEIGHT	0.5KG
NOMINAL LUMENS	1400lm	HARDWARE	GLASS LENS, O-RING, GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

**Product Generator:** example 9007-AB-M-30-RF-9W-DALI-HC

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL9007	AB Aged Brass	N Narrow 10°	27 2700K	RF Recessed Floor	9W / 350mA	DALI	HC Honeycomb Louver
	BR Brushed Brass	M Medium 21°	30 3000K	RW Recessed Wall		0-10V	DL Diffuser Lens
	SS Stainless Steel	W Wide 33°	40 4000K			Phase	EL Elliptical Lens
	CC Custom					On/Off	SL Spread Lens
							RS Recessing Sleeve
							CAN Surface Can

NL9007	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---