


FLEX 15 VERTICAL RGB



LUMINAIRE SPECIFICATION

Width	15mm
Height	15mm
Maximum length	5m and 13m options
Cut interval	100mm
Minimum bend diameter	>120mm
Material	White silicone
Mounting	Surface
IP Rating	IP67
Protection	UV, flame, salt and chlorine resistant
Standards	EN/AS/NZS 60598-2-1, 62031, 62471
Warranty	5 Years

LED SPECIFICATION

LED Wattage	12W/m
CCT	RGB
Lumen package RGB	R : 70lm/m, G : 150lm/m, B : 30lm/m
Lifetime (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
Driver requirement	Constant voltage
Voltage	24VDC

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	CONNECTOR IP	CABLE LENGTH	LENGTH
63S15V Neon Flex 15 Vertical	1 White	RGB RGB	S12 12W/m (5m max.) L12 12W/m (13m max.)	E End B Bottom SL Side Left SR Side Right	7 IP67	003 0.3m 010 1m 030 3m 050 5m 100 10m	.XXXX Length in mm
63S15V	1	RGB			7		