


FLEX 20 VERTICAL DOMED DMX PIXEL RGBW



LUMINAIRE SPECIFICATION

Width	20mm
Height	18mm
Maximum length	5m with 10m input cable 8m with 0.5m input cable
Cut interval	100mm
Minimum bend diameter	>300mm
Material	White silicone
Mounting	Surface
IP Rating	IP67
Protection	UV, flame, salt and chlorine resistant
Standards	EN/AS/NZS 60598-2-1, 62031, 62471
Warranty	5 Years

LED SPECIFICATION

LED Wattage	16W/m
LED Type	DMX Pixel
LED Qty	60 LEDs/m
Pixel Qty	10 Pixels/m
CCT	See options table below
Lifetime (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
Driver requirement	Constant voltage
Voltage	24VDC

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	CONNECTOR IP	CABLE LENGTH	LENGTH
63S20VD Neon Flex 20 Vertical Domed	1 White	RGBW27 RGBW-2700K RGBW30 RGBW-3000K RGBW40 RGBW-4000K RGBW60 RGBW-6000K	DMX10P16 16W/m 10P/m	E End B Bottom SL Side Left SR Side Right	7 IP67	003 0.3m 010 1m 030 3m 050 5m 100 10m	.XXXX Length in mm
63S20VD	1		DMX10P16		7		